# Design & Brand Guidelines.



### **Company Adress**

Nibelungengasse 8/5 1010 Vienna, Austria

### Web

contact@koga-energy.com www.koga-energy.com

# LOGO CONSTRUCTION & CLE

In logo usage, the required negative space gaps should be as shown below. The smallest usage ratio is also specified.





The ratios of KOGA and Energy graphic elements are determined as shown on the side.





The KOGA logo should be used in the colors (male - female) lightness on the backgrounds shown below and similar variations of these backgrounds.













# LOGOGRID & CLE

The logo should not be used in the ways shown below. It should not be crushed, and its proportion and balance should not be altered. The color balance should not deviate from the lightness shown on the previous page.





The logo can be used in gold leaf or foil on different materials as shown below. When used on different surfaces, additional approval must be obtained from the relevant authorities.



CORPORATE COLORS

The selected colors and color descriptions for KOGA Energy are as follows. The Green RAL color is chosen for conditions where it is very necessary and vital to use. When RAL is needed, it is recommended to use the logo in a single color, gray.

PRIMARY COLORS

COLOR CODES

Green

**PANTONE** 

7745

RAL

6025 Frangrün (In case of oblication otherwise gray should be preferred for RAL)

СМҮК

C35 - M09 - Y90 - K15

**RGB** 

R154 - G170 - B62

**HEX** 

#99aa3e

Dark Grey

**PANTONE** 

Cool Gray 10

RAL

7012 Basaltgrau

**CMYK** 

C00 - M00 - Y00 - K75

RGB

R100 - G100 - B100

HEX


#646464


COLOR TINTS

The color tint ratios can be as shown in the example below. Additionally, a secondary light gray shade has been determined below for use when needed.

# SECNDARY COLOR AND COLOR TONES

# LightGrey





USAGE

**CMYK** C00 - M00 - Y00 - K50

DESIGN &
BRAND GUIDELINES.



# **Company Adress**

Nibelungengasse 8/5 1010 Vienna, Austria

# Web

contact@koga-energy.com www.koga-energy.com